



LED Twin Spot Luminaires

Surface mounted TS-EL2053



Product Features

- Surface mounted design
- 2 x 0.5W LED twin spot luminaires
- High quality LED chips
- Minimum 100,000 Hours lamp life
- Non-Maintained type
- Fault indication
- Change over complete in less than 1 second
- Ni-Cd or Ni-MH rechargeable high temperature battery for emergency backup purpose
- 2 or 3 Hours battery backup
- Provided with "TEST" button for regular maintenance check
- Adjustable lamp head
- IP20 protection

Standards

- BS 5266 Part 1
- BSEN 60598 2-22
- F.S.D PPA/104(A) (4th Revision)

Product Specification

Model	TS-EL2053
Lamp Type	LED
Luminaires Type	Non-Maintained Type
Power Consumption	2 x 0.5W
Main Supply	AC220 ~ 240V AC, +/- 6%, 50/60 Hz
Battery Type	3.6V, 0.8Ah Sealed Ni-Cd Rechargeable Battery
Emergency Duration	2 Hours
Battery Recharge Duration	Less than 12 hours
LED Life Span	>50,000 Hours
Insulation Class	Class one Earthing
Temperature Range	0 - 40 Celsius
Dimension (mm)	L265 x H280 x W70
Ingress Protection	IP20

Product dimension

